


## Accessories for actuator/sensor cables – male flange with solder contacts, rear-mounted



Typecode **M12A12MBRB9SC011**

ID **1006010000099**

### Technical Data\*

Connector A	
Connector	M12, Male, A-Coding
Number of Pins	12-Pin
Contacts	Brass, Gold-plated
Flange housing	Brass, Nickel-plated
Mounting type	Rear-mounted
Contact Carriers	PA
Seal	FKM
Protection Class	IP67, Only in screwed condition
Mechanical lifespan	≥ 100 Mating cycles
Pollution degree	3
Screw-in thread	PG9
Connection mode	Solder contact
Wiring specification	26 AWG
Standard	IEC 61076-2-101

### Electrical properties at +20 °C

Rated Voltage	30 V
Rated current	1.5 A
Rated impulse voltage	0.5 kV
Contact resistance	≤ 3 mΩ
Insulation resistance	≥ 100 MΩ

### Mechanical and chemical properties

Ambient temperature range (stationary) -40 °C ... 120 °C

### Commercial data


Weight	g
Country of origin	CN
Packaging unit	1 pc

\* Please note that the data specified here were design data, and the parameters of product are subject to changes without prior notice. Matters not mentioned herein. Please contact customer service. Please also note that the user is responsible for validating functionality, conformity with applicable laws and directives, as well as for the electrical safety in the particular application.

### Features

- M12, Male, 12-Pin
- Rear-mounted
- Protection Class: IP67
- RoHS-compliant
- Metal housing
- Solder contact

### Contact assignment



### Through bore

